



NAC67Y(hydraulic)&NAC67K(cnc) Series Performance & Data of Hydraulic Bending Machine

Features of WC67Y Hydraulic Bending Machine:

1. Three-cylinder structure, multi cylinder structure adopted when machine above 4 meters
2. Schneider Electric
3. BOSCH composite hydraulic system
4. Upper mold wedge clamping
5. With digital display on foot switch control
6. Inward seal components with high quality
7. Permit fine micro adjustment with mechanical back gauge device and ram stroke, with a counter displaying



Specifications:

Model	40/2000	40/2500	63/1600	63/2500	100/3200	
Nominal pressure of machine(KN)	400	400	630	630	1000	
Length of working table(mm)	2000	2500	1600	2500	3200	
Distance between horsing(mm)	1640	2050	1340	2100	2600	
Throat depth(mm)	200	200	200	250	320	
Ram stroke(mm)	100	150	100	100	150	
Max.open height between working table and ram(mm)	360	360	360	360	410	
Power of main motor(kW)	4	5,5	5,5	5,5	7,5	
Overall dimensions L*W*H(mm)	2060*1660*2050	2600*1660*2050	1700*1500*2010	2600*1690*2350	3260*1753*2500	
Weight of machine(kg)	3300	3500	3000	4220	8000	
Model	100/4000	125/3200	160/3200	160/4000	200/4000	
Nominal pressure of machine(KN)	1000	1250	1600	1600	2000	
Length of working table(mm)	4000	3200	3200	4000	4000	
Distance between horsing(mm)	3300	2600	2600	3300	3300	
Throat depth(mm)	320	320	320	320	320	
Ram stroke(mm)	150	150	200	200	200	
Max.open height between working table and ram(mm)	415	415	465	465	465	
Power of main motor	7,5	7,5	11	11	11	
Overall dimensions L*W*H(mm)	4060*1790*2500	3280*1790*2600	3260*1930*2800	4060*1930*2800	4060*1930*2800	
Weight of machine(kg)	10000	9000	10500	14000	15000	
Model	200/6000	250/4000	300/3200	320/4000	320/6000	500/8000
Nominal pressure of machine(KN)	2000	2500	3200	3200	3200	5000
Length of working table(mm)	6000	4000	3200	4000	6000	8000
Distance between horsing(mm)	5500	3300	3300	3300	5500	6800
Throat depth(mm)	380	320	400	400	400	415
Ram stroke(mm)	200	200	250	250	200	240

Max.open height between working table and ram(mm)	465	465	560	560	465	520
Power of main motor	11	15	22	22	18,5	37
Overall dimensions L*W*H(mm)	6100*1950*2900	4060*2340*3200	3200*2570*3560	4060*2570*3560	6100*1800*2700	8000*2700*3300
Weight of machine(kg)	25000	21000	2200	24500	31000	48000